

6165 W Detroit St. • Chandler AZ 85226
+1 (602) 276-0406 • +1 (800) 528-8242 • FAX +1 (480) 961-0513
www.crafco.com

READ BEFORE USING THIS PRODUCT

GENERAL

Reactive Form Release No Odor is a film forming treatment that prevents the bonding of fresh concrete mix to forms, tools, and equipment. Composed of non-staining natural oils, Reactive Form Release No Odor reacts with excess lime on the surface of the concrete to give a quick, clean stripping from any form work. Max VOC 150 g/L

RECOMMENDED USES

Reactive Form Release No Odor is recommended for use on various types of forms such as wood, steel, and fiberglass. Also, this form oil is suited to be used on aluminum forms.

SPECIFICATION CONFORMANCE

This product is below, the maximum VOC content limit for form release compounds as required by the U.S. EPA Architectural Coatings Rule and the rigid specifications set forth by the Ozone Transport Commission (OTC).

INSTALLATION INSTRUCTIONS

Treat and season forms prior to each use with brush, roller, or hand sprayer. Do not exceed 30 PSI with fan type sprayer. Avoid excess run-off or ponding by only applying a thin coat. Coverage rate is approximately 600-1000 ft²/gal (14.7–24.5 m²/L) for plywood/lumber forms and 1000-2000 ft²/gal (24.5–49.1 m²/L) for aluminum/steel forms.

LIMITATIONS

- For exterior use only
- Not to be used as tilt-up bond breaker
- Adequate ventilation necessary during application

PACKAGING

275 Gal. (1041 L) totes, 55 Gal. (208.2 L) drums, 5 Gal. (18.9 L) pails

STORAGE

- Storage temperature range 40 °F (4 °C) minimum
- Dispose of container in accordance with state and federal regulations

WARRANTY

CRAFCO, Inc. warrants that CRAFCO products meet applicable ASTM, AASHTO, Federal or State specifications at time of shipment. Techniques used for the preparation of the pavement are beyond our control as are the use and application of the products; therefore, Crafcoco shall not be responsible for improperly applied or misused products. Remedies against Crafcoco, Inc., as agreed to by Crafcoco, are limited to replacing nonconforming product or refund (full or partial) of purchase price from Crafcoco, Inc. All claims for breach of this warranty must be made within three (3) months of the date of use or twelve (12) months from the date of delivery by Crafcoco, Inc. whichever is earlier. There shall be no other warranties expressed or implied. **For optimum performance, follow Crafcoco recommendations for product installation.**