CRAFCO[®] INC

SAFETY DATA SHEET

1. Identification

Product identifier Crafco Asphalt Primer

Other means of identification None.

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer: Crafco, Inc.

Address: 6165 West Detroit St.

Chandler, AZ 85226 USA

Contact Name: Crafco Materials Engineering

Telephone: 602-276-0406 **E-mail:** sales@crafco.com

CHEMTREC: 800-424-9300 (North America)

+ 1-703-527-3887 (International)

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3

Health hazards Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified. **OSHA defined hazards** Not classified.

Label elements



Signal word Warning

Hazard statement Flammable liquid and vapor. May cause drowsiness or dizziness.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. No smoking. Keep container

tightly closed. Avoid breathing mist/vapors/spray. Ground/bond container and receiving

equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Use

only outdoors or in a well-ventilated area.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire:

Use appropriate media for extinction.

Storage Store in a well-ventilated place. Keep cool.

None known.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

See section 13 of this SDS for disposal instructions.

Hazard(s) not otherwise

classified (HNOC)

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	40 - 60
PETROLEUM NAPHTHA		64741-44-2	40 -60

Material name: Crafco Asphalt Primer sps us

5731 Version #: 04 Revision date: 05-29-2020 Issue date: 12-11-2014

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing

difficulties, oxygen may be necessary. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if

needed.

Skin contact For hot product, immediately immerse in or flush the affected area with large amounts of cold

water to dissipate heat. For minor skin contact, avoid spreading material on unaffected skin. Wash

off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO

NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and

persists.

Not available.

Ingestion Rinse mouth thoroughly. Call a POISON CENTER or doctor/physician. Do not induce vomiting

without advice from poison control center. If vomiting occurs, keep head low so that stomach

content doesn't get into the lungs.

Most important

General information

symptoms/effects, acute and

delayed
Indication of immediate

medical attention and special treatment needed

In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation.

Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

lia

Specific hazards arising from the chemical

Special protective equipment and precautions for

firefighters
Fire fighting

equipment/instructions

Foam. Carbon dioxide (CO2). Water fog. Dry chemical powder.

Do not use water jet.

Fire may produce irritating, corrosive and/or toxic gases.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Do not get water inside container. Some of these materials, if spilled, may evaporate leaving a flammable residue.

Specific methods In the event of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Methods and materials for containment and cleaning up

Keep unnecessary personnel away. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

Stop the flow of material, if this is without risk. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Never return spills in original containers for re-use.

Environmental precautionsPrevent further leakage or spillage if safe to do so. Do not contaminate water. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response

Center.

7. Handling and storage

Precautions for safe handling

Avoid heat, sparks, open flames and other ignition sources. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Do not use in areas without adequate ventilation. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container closed. Keep container dry. Keep away from food, drink and animal feedingstuffs. Keep out of reach of children. Use care in handling/storage.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components **Type** Value **Form** ASPHALT (CAS 8052-42-4) **TWA** 0.5 mg/m3 Inhalable fume.

US. NIOSH: Pocket Guide to Chemical Hazards Components **Type**

Value ASPHALT (CAS 8052-42-4) Ceiling 5 mg/m3 Fume.

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

Form

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

It is a good industrial hygiene practice to minimize skin contact. Wear appropriate clothing to Other

prevent any possibility of liquid contact and repeated or prolonged vapor contact.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Not available.

General hygiene considerations

When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Handle in accordance with good

industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance Viscous liquid

Physical state Liquid. **Form** Liquid.

Color Brown - black

Odor Mild Petroleum Odor

Odor threshold Not available. Not available. Melting point/freezing point Not available. Initial boiling point and 257 °F (125 °C)

boiling range Flash point

> 57.0 °F (> 13.9 °C) Closed Cup

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower Not available.

(%)

Flammability limit -

Not available.

upper (%)

Explosive limit - lower

Not available.

(%)

Explosive limit - upper

Not available.

(%)

Vapor pressure Not available.

Vapor density > 1

Material name: Crafco Asphalt Primer 5731 Version #: 04 Revision date: 05-29-2020 Issue date: 12-11-2014 **Relative density** Not available.

Solubility(ies)

Solubility (water)Not available.Partition coefficientNot available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.Viscosity50 - 400 cPViscosity temperature77 °F (25 °C)

Other information

Molecular weight 250 lb/lb-mole estimated

 Specific gravity
 0.83 - 0.92

 VOC
 413 g/l

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Stable at normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. **Incompatible materials** Strong oxidizing agents.

Hazardous decomposition

products

Irritants. Carbon oxides. Sulphur oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis

Eye contact May be irritating to eyes.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

Acute toxicity Not classified.

Skin corrosion/irritation May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Serious eye damage/eye

irritation

Not classified. May be irritating to eyes.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization Not a skin sensitizer.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity None of this product's components are listed by ACGIH, IARC, NIOSH, NTP or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

PETROLEUM NAPHTHA (CAS 64741-44-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Not classified.

Specific target organ toxicity Central nervous system.

- single exposure

Specific target organ toxicity

- repeated exposure

Not available.

Aspiration hazard Not classified.

Chronic effects Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Persistence and degradability Not available.

Bioaccumulative potential Not available.

Mobility in soil Not available.

Other adverse effects Not available.

13. Disposal considerations

Disposal instructionsDispose of contents/container in accordance with local/regional/national/international regulations.

If discarded, this product is considered a RCRA ignitable waste, D001.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Waste from residues /

unused products

Dispose of in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number UN1999

UN proper shipping name Tars, liquid including road oils and cut back bitumens

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group II

Special precautions for Not available.

user

Special provisions 149, B13, IB2, T3, TP3, TP29

Packaging exceptions 150
Packaging non bulk 202
Packaging bulk 242

IATA

UN number UN1999

UN proper shipping name Tars, liquid including road asphalt and oils, bitumen and cut backs

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards No.
ERG Code 3L

Special precautions for

user

Not available.

Daggaran and a

Passenger and cargo Allowed with restrictions.

aircraft

Other information

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1999

UN proper shipping name TARS, LIQUID including road oils, and cutback bitumens

Transport hazard class(es)
Class 3
Subsidiary risk Packing group II

Packing group
Environmental hazards

Marine pollutant No.

Material name: Crafco Asphalt Primer
5731 Version #: 04 Revision date: 05-29-2020 Issue date: 12-11-2014

EmS F-E, S-E Special precautions for Not available.

Transport in bulk according to Not available. Annex II of MARPOL 73/78 and the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ASPHALT (CAS 8052-42-4) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure) Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

Hazard not otherwise classified (HNOC)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Material name: Crafco Asphalt Primer 5731 Version #: 04 Revision date: 05-29-2020 Issue date: 12-11-2014 Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65

California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ASPHALT (CAS 8052-42-4)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 12-11-2014

 Revision date
 05-29-2020

Version # 04

NFPA ratings Health: 2

Flammability: 3 Instability: 0

References ACGIH

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Composition / Information on Ingredients: Disclosure Overrides

Physical & Chemical Properties: Multiple Properties

HazReg Data: International Inventories

GHS: Classification

Material name: Crafco Asphalt Primer

SDS US

5731 Version #: 04 Revision date: 05-29-2020 Issue date: 12-11-2014