



SPECIFICATIONS

43300 SUPER SHOT™ 60 (PROPANE) WITH PUMP ON DEMAND FEATURES

6165 W. Detroit St. • Chandler AZ 85226
 +1 (602) 276-0406 • +1 (800) 528-8242 • FAX +1 (480) 961-0513
 www.crafco.com

DECEMBER 2021

The purpose of these specifications is to describe a double-boiler type melter applicator that is specifically designed for and shall be capable of heating and applying all grades of asphalt rubber sealant, fiber modified asphalt sealant and specification joint sealant without any further equipment modification. It may be used for the application of resinous, colored sealant and fillers. This unit shall be the manufacturer's current production model manufactured in the United States of America.

	<u>Comply</u>	<u>Does Not Comply</u>
1. GENERAL SPECIFICATIONS		
A. The machine shall be capable of dispensing sealant material within one hour of start up at a 70° F (21.1° C) ambient temperature.	_____	_____
B. All qualified bidders must have and maintain a complete inventory of replacement parts and have experienced factory-trained service personnel for this equipment.	_____	_____
C. A comprehensive safety manual and operational/maintenance CD shall be supplied with each unit.	_____	_____
D. A factory-trained person shall be made available for initial start-up and training in the operation of the melter.	_____	_____
E. Temperature indicating devices shall have intervals no greater than 1° F (2.8° C) and shall be calibrated as required to assure accuracy.	_____	_____
F. The melter shall have continuous sealant agitation and a mixing system to provide uniform viscosity and temperature of material being applied.	_____	_____
2. REQUIRED SAFETY FEATURES		
A. The unit shall have a safety shut-off on the lid that automatically stops the agitator when the lid is opened.	_____	_____
B. The applicator wand shall be equipped with an automatic shut-off feature that will stop the rotation of the sealant pump, sealant flow, and all line pressure when the handle is released or dropped.	_____	_____
C. The heat transfer oil shall adequately and efficiently bring the sealant material to application temperature without the use of a heat transfer oil circulation pump. This eliminates the potential exposure of personnel to pressurized hot heat transfer oil.	_____	_____
D. The material tank meets all FMCSA requirements for elevated temperature materials by meeting CFR Title 49, Part 173.247.	_____	_____

	<u>Comply</u>	<u>Does Not Comply</u>
--	---------------	----------------------------

Other: _____

3. TOWING FRAME AND JACK

- A. This unit shall be trailer mounted. The longitudinal side frames and tongue members of the trailer shall be of one continuous piece construction composed of hot rolled steel channel having the minimum dimensions of 3 inches (7.62 cm) web, 3/16 inch (.48 cm) thickness with 1.41 inch (3.58 cm) flanges.
- B. The configuration of the channel shall be cold formed with the flanges on the outside resulting in a one-piece frame member with no cross welding of or on the flanges to avoid any possibility of flange stress cracking.
- C. The tongue shall be equipped with an appropriate heavy-duty ball or pintle hitch and shall be adjustable in height above ground level from a minimum of 14 inches (35.6 cm), to a maximum of 32 inches (81.3 cm), permitting practically level towing with a wide range of towing vehicles. The towing hitch shall be bolted to the hitch plate for easy conversion to other type hitches.
- D. A screw-post tongue jack shall be furnished. It shall have a caster wheel and a capacity of 500 pounds (226.8 kg). It shall be side mounted and swing away for positive road clearance while under tow.

Other: _____

4. TRAILER RUNNING GEAR

- A. The unit shall be equipped with a single rubber torsional axle with a safe load capacity of 3,200 pounds (1452 kg) and have two ST185/80 D-13 tires. Trailers with springs and shackles are unacceptable as they require more maintenance and reduce ground clearance.
- B. The unit shall have dual LED taillights, stoplights and turn signals. Lights shall be ICC approved. A license plate holder shall be attached to the driver's side taillight.
- C. All melter fluid tanks shall be positioned no lower than the deck level and mounted on top of the channel frame members to assure proper ground clearance. Units that have components that extend below the trailer frame are unacceptable.
- D. The unit shall also be equipped with two safety chains not less than 48 inches (121.9 cm) of .38 inch (.97 cm) coil proof chain attached to the tongue with a drilled type clevis pin on the end attached to the frame and screw type clevis pin on the opposite end.
- E. Total shipping weight is approximately 2,200 pounds (997.9 kg).

Comply Does Not Comply

Other: _____

5. HEATING TANK

- A. The material heating tank shall be a minimum of 30 inches (76.2 cm) in diameter by 19 inches (48.3 cm) deep having a minimum capacity of 58.7 gallons (222.2 l) at ambient temperature. Oval or square sided tanks are unacceptable as they allow for uneven agitation resulting in a non-homogenous sealant and uneven heating of sealant. _____
- B. The tank will have a rear discharge from the pump and a rear plugged outlet. A double boiler type jacket shall create a reservoir that shall hold a minimum of 21 gallons (79.5 l) and require no more than 25 gallons (95 l) of heat transfer oil at 70° F (21.1° C). (Note: At 500° F (260° C) the heating oil will expand approximately 18%). _____
- C. The jacket shall wrap around 100% of the outside area of the circular material tank and bottom and allow for complete circulation of the heated transfer oil. _____
- D. The tank and jacket shall be made of not less than 3/16 inch (.94 cm) rolled sheet steel. _____
- E. There shall be one plug to allow the entire heat transfer oil system to be drained. _____
- F. The heat transfer oil shall be of ISO grade 68. _____

Other: _____

6. EXPANSION TANK

- A. A vented expansion tank for heat transfer oil. Overflow down tubes are unacceptable. _____

Other: _____

7. HYDRAULIC SYSTEM

- A. The hydraulic system shall incorporate a hydraulic pump to power the agitation and pumping system. Belt driven hydraulics is unacceptable. _____
- B. All valves shall be solenoid operated by toggle switch and wand handle switch. _____
- C. The controls will allow for bi-directional operation of the sealant pump and agitator. _____
- D. A flow control valve will be mounted on the rear of the unit to allow the operator to adjust the pump operational speed. _____

<u>Comply</u>	<u>Does Not Comply</u>
---------------	----------------------------

E. The minimum 26 gallon (98.4 l) hydraulic tank will be equipped with an internal 10-micron full flow filter. The filter shall be equipped with a restriction indicator to indicate the need for service. A sight gauge level indicator equipped with a thermometer to measure oil temperature will be mounted on the tank and located where it is easily viewed.

_____	_____
-------	-------

Other: _____

_____	_____
-------	-------

8. TANK INSULATION

A. The heating tank shall be insulated with a minimum of 1-1/2 inch (3.81 cm) thick high temperature ceramic insulation and covered by a 22 gauge (.07 cm) steel outer wrapper. Fiberglass and rock wool insulation are unacceptable due to their moisture retention properties resulting in a significant loss of their insulating value over an eighteen-month period.

_____	_____
-------	-------

Other: _____

_____	_____
-------	-------

9. LOADING HATCH

A. A low profile opening for loading shall be required at the top of the material tank and shall be located on the curbside of the machine for operator safety. The loading height shall be a minimum of 50 inches (127 cm) and shall not exceed 54 inches (137 cm) for correct ergonomic lifting and fume exposure.

_____	_____
-------	-------

B. This will allow the operation of the equipment, including sealant loading, from curbside. Loading systems that require the operator to step onto the melter are unacceptable.

_____	_____
-------	-------

C. The opening shall have a minimum area of 180 square inches (1,161 square cm), while not exceeding 200 square inches (1290 square cm) in order to prevent heat loss, and shall be hinged to allow placement of a block of sealant onto lid and closure of lid for easy, anti-splash loading.

_____	_____
-------	-------

Other: _____

_____	_____
-------	-------

10. HEATING SYSTEM

A. The heat transfer oil is heated by one (1) 180,000 BTU vapor fuel LP burner directly at the bottom of the heat transfer oil tank.

_____	_____
-------	-------

B. Total area exposed to the burner shall be a minimum of 3,335 square inches (21,516 square cm). The material tank shall have a minimum of 2,538 square inches (16,374 square cm) of contact with the heat transfer oil. No other mechanical circulation of the heat transfer oil by pump shall be accepted. This provides for a melt rate of 480 pounds (217.7 kg) per hour.

	<u>Comply</u>	<u>Does Not Comply</u>
--	---------------	----------------------------

Other: _____

	_____	_____
--	-------	-------

11. IGNITION OF BURNER

- A. The burner shall be lit by an electric spark igniter. This igniter shall work in conjunction with a sensor that detects a lack of burn or ignition and shuts down the fuel supply. The thermostat control is located on the curbside of the machine for operator safety.

	_____	_____
--	-------	-------

Other: _____

	_____	_____
--	-------	-------

12. TEMPERATURE CONTROL

- A. The melter applicator shall have a thermostatic control device that will automatically regulate hot oil, material, and hose temperature.
- B. The control shall have a digital readout for temperatures of hot oil, material, and hose.
- C. The thermostat shall control burner ignition for a temperature range from a low of 200° F (93.3° C) up to a high of 425° F (218.3° C) for a wide variety of sealants.
- D. The temperature controls shall be in a single weatherproof control box.
- E. The controls shall be activated by a single power switch, which will then turn each function on at the proper time.
- F. The controls will automatically turn power on to the agitation system when the material reaches 275°F (135°C).
- G. The controls will automatically start the hose heating system when the material temperature reaches 275°F (135°C).
- H. The controls will automatically activate the application (pumping) system when the hose temperature reaches 325°F (162.8°C).
- I. The controls will lock out operation of the agitation system, hose heating system, and application system when the material temperature is below the minimum operation temperature for operator safety and to prevent damage to the operational components.

	_____	_____
--	-------	-------

	_____	_____
--	-------	-------

	_____	_____
--	-------	-------

	_____	_____
--	-------	-------

	_____	_____
--	-------	-------

	_____	_____
--	-------	-------

	_____	_____
--	-------	-------

	_____	_____
--	-------	-------

	_____	_____
--	-------	-------

Other: _____

	_____	_____
--	-------	-------

13. DRIVE AND DRIVE CONTROLS

- A. The motive force to the agitator and material pump shall be hydraulic motors driven by a single hydraulic pump.

	_____	_____
--	-------	-------

	<u>Comply</u>	<u>Does Not Comply</u>
--	---------------	------------------------

- | | | |
|--|-------|-------|
| B. The drive controls governing the rotational speed of the material pump shall be controlled by adjustable hydraulic valves. | _____ | _____ |
| C. The drive controls governing the rotational speed of the material pump shall be controlled by adjustable hydraulic valves. | _____ | _____ |
| D. The material pump will have infinite speed control and is electrically actuated by a toggle switch on the control panel or a switch on the hand wand. | _____ | _____ |
| Other: _____ | _____ | _____ |

14. AGITATION

- | | | |
|---|-------|-------|
| A. The sealant material shall be mixed by a hydraulically driven, full sweep vertical agitator with two opposing horizontal paddles and vertical risers attached to the ends. This feature ensures that material remains in complete suspension and that the hot material stays in the lower area of the tank and does not get splashed or thrown to the upper areas of the tank. | _____ | _____ |
| B. The agitation system shall be chain driven from the hydraulic motor to the agitator. | _____ | _____ |
| C. The agitator rotates in both directions. | _____ | _____ |
| D. For additional safety the agitator will shut off automatically when the loading hatch is opened. | _____ | _____ |
| Other: _____ | _____ | _____ |

15. BI-DIRECTIONAL VARIABLE SPEED PUMPING UNIT

- | | | |
|---|-------|-------|
| A. A hardened steel gear pump is located in the center of the material tank attached to the bottom of the tank. | _____ | _____ |
| B. Pumping of material is controlled by a switch on the hand wand and output is controlled hydraulically. | _____ | _____ |
| C. The pump and agitator drive shaft stands vertically attached to two motors on the top surface of the tank. | _____ | _____ |
| D. One motor rotates an axial tube having radial mixing blades at the chamber bottom. | _____ | _____ |
| E. The second motor drives a coaxial shaft running through the tube to the pump. | _____ | _____ |
| F. Sealant pumping shall be on demand. | _____ | _____ |

	<u>Comply</u>	<u>Does Not Comply</u>
G. When pumping stops, all line pressure and sealant flow shall stop.	_____	_____
H. No external plumbing or recirculation back into the tank is acceptable.	_____	_____
I. No internal or external valves shall be used in the pumping and sealant delivery system.	_____	_____
J. The pump shall be capable of delivering sealant at a rate that exceeds the melt rate of the unit.	_____	_____
Other: _____ _____	_____	_____

16. ACTIVE PUMP PROTECTION

A. The pump shall be completely encircled by a protective screen.	_____	_____
B. The screen shall not allow anything larger than 1/2 inch (1.27 cm) in size to pass from the sealant tank into the pump suction port.	_____	_____
C. The screen shall continuously rotate 360° around the pump whenever the sealant agitator is engaged.	_____	_____
D. The active screen will protect the pump from foreign object damage and will self-clean as it rotates around the sealant pump and suction port.	_____	_____
Other: _____ _____	_____	_____

17. SEALANT HOSE AND APPLICATOR WAND

A. Both the hose and wand are heated by 24 VAC voltage electric current and are temperature regulated.	_____	_____
B. The combination length between the hose and wand shall not be less than 19 feet (5.79 m).	_____	_____
C. Due to weight and safety considerations, an oil-jacketed hose is unacceptable.	_____	_____
D. The hose shall be specifically manufactured for handling liquid asphalt products up to 500° F (260° C) at 500 psi (34.47 bar) working pressure.	_____	_____
E. Hose shall not be less than 15 feet (4.57 m) in length.	_____	_____

	<u>Comply</u>	<u>Does Not Comply</u>
F. For maximum operator safety it shall be made of 3/4 inch (1.91 cm) inside diameter PTFE Teflon® inner core and reinforced with a stainless steel outer braid. This braid serves a dual purpose; it provides a protective covering for the inner core and allows the hose to carry pressure. It shall also be insulated and have a cover to prevent damage to the hose or allow hot material from leaking out. Further, it shall have an abrasive sleeve to protect the operator from heat.	_____	_____
G. Total diameter of the hose shall be not greater than 2 ¼ inch (5.72 cm). The total weight of the hose shall not exceed 20 pounds (9.07 kg).	_____	_____
H. The hose is to be wrapped with a minimum of three electrical wires with terminal ends. The wires will be capable of heating the hose to 400°F (204° C) in less than 45 minutes and have variable temperature control capability.	_____	_____
I. The hand wand shall not be less than 4 feet (1.22 m) in length.	_____	_____
J. The hand wand shall be constructed of steel with sufficient strength to withstand normal day-to-day operation.	_____	_____
K. Material flow is controlled by a trigger switch.	_____	_____
L. For greater operator mobility, the connection between the wand and hose shall be through a 360° swivel.	_____	_____
M. There shall be no obstruction or valves between the material pump and the wand end.	_____	_____
N. The hose is supported by a 6 ft. boom (1.83 m), which swivels side to side on dual pillow block bearings.	_____	_____
O. The boom is centered at the rear of the machine.	_____	_____
Other: _____	_____	_____

18. ENGINE

The unit shall be equipped with a propane engine complying with the following specifications:

- Electronic Ignition
- Four Cycles, V Twin 21.5 HP (16kw) @ 3600 RPM
- 2.64" (67 mm) Stroke
- 44 cu. In, (725 cu cm) Displacement
- 3.3" (83 mm) Bore
- 9.0 to 1 Compression Ratio
- High efficiency air cooling fans
- Overhead valve design and hydraulic valve lifters
- Full-pressure oil flow lubrication with 4 pints (1.91 liters) oil capacity

<u>Comply</u>	<u>Does Not Comply</u>
---------------	----------------------------

Other: _____

19. FUEL CAPACITY

A. The melter shall have a 100 pound (45.4 kg) vapor propane bottle supplied for operation of the entire unit.

_____	_____
-------	-------

B. The unit will be capable of operating for one working day on one tank of fuel.

_____	_____
-------	-------

Other: _____

_____	_____
-------	-------

20. PAINT

A. All painted surfaces shall be coated with Axalta two-part epoxy paint applied by Axalta certified painters.

_____	_____
-------	-------

Other: _____

_____	_____
-------	-------

21. TRAINING

A. An authorized, factory representative will be made available for a full day of training at a facility designated by the bidding agency.

_____	_____
-------	-------

B. At this training session a complete operational, mechanical and safety overview will occur.

_____	_____
-------	-------

C. Both safety and operational manuals will be viewed and discussed with all concerned personnel.

_____	_____
-------	-------

D. Additionally, the representative will be available at that time for "on the job" safety and field training.

_____	_____
-------	-------

Other: _____

_____	_____
-------	-------

22. SAFETY AND TRAINING MANUALS

A. A written Safety Manual will be provided to the bidding agency.

_____	_____
-------	-------

23. PARTS

A. Bidders must show proof that a large stock of parts for the model of equipment upon which he is bidding is maintained at his facility.

_____	_____
-------	-------

24. AWARD

A. Equipment is for use by the Highway Department and must meet the requirements of that agency as interpreted by the Highway Commissioner.

_____	_____
-------	-------

<u>Comply</u>	<u>Does Not Comply</u>
---------------	----------------------------

- | | | |
|--|-------|-------|
| B. Prior to award, the Purchasing Agency may require a visit to the supplier's facility to assure supplier has plant capacity to manufacturer and deliver equipment on time as required. | _____ | _____ |
| C. If it is determined that the supplier cannot supply as requested, this is just cause for cancellation. | _____ | _____ |

25. WARRANTY

- | | | |
|--|-------|-------|
| A. The manufacturer shall warranty the equipment for two years or as otherwise noted in the manufacturer's standard warranty policy. | _____ | _____ |
|--|-------|-------|

26. QUALIFICATIONS OF BIDDERS

- | | | |
|--|-------|-------|
| A. No bid will be considered unless the bidder can meet the following conditions: | _____ | _____ |
| B. Bidder must have a parts/service location and keeps a sufficient stock of parts on hand at all times. | _____ | _____ |
| C. The equipment offered is the stock model chassis that meets the requirements of the specifications without material changes or modifications. | _____ | _____ |
| D. The model is regularly advertised and sold by the manufacturer. | _____ | _____ |
| E. The bidder has been engaged in the sale and support of this make and model of equipment for at least twenty-four months. | _____ | _____ |

OPTIONS REQUIRED (X if to be included)

(Customer to insert quantity for each option required)

- 20018 - 2 5/16 inch Ball Hitch
- 20016 - 2 ½ inch Pintle Hitch
- 20017- 2 inch Ball Hitch
- 20014 - 3 inch Pintle Hitch
- Sealant Tip Adapter
- 3 inch Applicator Disk
- V-Shaped Squeegee (Qty.____)
- 1/2 inch Round Sealing Tip
- 52400 - Extra Electric Hose
- Extra Hydraulic Filter
- 24086 - Lockable Battery Cover
- 50772 - Lockable Engine Cover
- 26098 - Tool Box
- 26058 - 10# Fire Ext. w/cover (Must order 26059 to mount)
- 26059 - Mounting Bracket for 10# Fire Ext.
- 26060 - 20# Fire Ext. w/cover (Must order 26061 to mount)
- 26061 - Mounting Bracket for 20# Fire Ext.
- Various Safety and Work Light kits, see brochure for more info
- Custom Paint
- 24227 – Seven Pin Flat Truck Connector (RV Style)
- 24007 – Five Pin Flat Truck Connector
- 24074 - Six Pin Round Truck Connector
- 24183 – Seven Pin Round Truck Connector
- 20120 - Hitch Extension, 18”
- 20140 - Hitch Extension, 28”
- 20150 - Hitch Extension, 39”
- 26119 – Safety Hook w/ Latch (2 Req'd)
- 44883 – Spare Tire Kit
- 24190K – 110V Overnight Heater
- 24194 – 220V Overnight Heater
- 43966K - Shot Timer Kit
- 55260 - Foot Pedal Kit
- 43416 – Gravity Feed Kit

APPROVED EQUAL

The approved make and model for this specification is a Crafc0 SS60. Bidders offering to supply equipment other than the approved make and model must supply a detailed description of the equipment being offered. Bidders offering to supply equipment other than the approved make and model shall also supply a list of references who have successfully heated, mixed and applied Crafc0 sealants through the equipment being offered. For purposes of comparison a separate list of all deviations to this specification must be attached to your bid document.

Prior to bid award an on-site demonstration of the equipment offered may be requested. All bidders offering other than the approved model listed will be required to provide an on-site demonstration at the agency's location within 7 days of request to verify that their unit complies with all specification requirements before their bid will be considered. Failure to carry out the provisions noted herein is deemed sufficient reason to reject the bidder's proposal.