



420 N. Roosevelt Ave. • Chandler AZ 85226
1-800-528-8242 • (602) 276-0406 • FAX (480) 961-0513
www.crafco.com

PRODUCT DATA SHEET
BAUXITE AGGREGATE
PART NO. 34950

JANUARY 2008

READ BEFORE USING THIS PRODUCT

GENERAL: Crafco Bauxite Aggregate is used as a high friction surface treatment for patching and overlay surface treatments. The aggregate remains sharp and retains a high skid resistance.

PROPERTIES:

Properties of Crafco Bauxite Aggregate are as follows:

<u>Property</u>		<u>Typical</u>	<u>Specification</u>
Color		Tan/Buf/Gray	---
Al ₂ O ₃ (%)		86	85 min.
Density (g/cm ³)		3.18	3.00 min.
Sieve Analysis (ASTM C136, % passing)	1/4"	100	100
	#4	100	99-100
	#8	73	45-85
	#10	55	20-65
	#16	4	0-7
	#30	0.5	0-0.5

INSTALLATION: Bauxite Aggregate can be applied by broadcasting by hand or machine. Consult the Product Data Sheet and Installation Instructions of the Crafco product that the Bauxite Aggregate is being used in conjunction with for specific usage details, coverage rates, application times and temperature conditions.

PACKAGING: Crafco Bauxite Aggregate is supplied in bags. Each bag contains 50lbs. of material.

STORAGE: Bags of Bauxite Aggregate must be stored in a dry location and be kept dry at all times. Wet or damp Bauxite Aggregate is not acceptable for use, since it may not adhere properly. Bauxite Aggregate shall be thoroughly dry prior to use.

SAFETY PRECAUTIONS: Before use, the crew should read and understand product safety information contained in the MSDS, which is supplied with each shipment. The MSDS describes the characteristics of the product as well as any potential health hazards and precautions for safe handling and use.